



Vanalar - Valves					Sıcaklığa (°C) göre max. Çalışma basıncı (bar)											
PN	Demir Döküm Cast Iron	Sfero Döküm Ductile Iron	Çelik Döküm Cast Steel	Çelik Steel	20 120'	200	250	300	350	400	425	450	500	520	550	
6	GG-25	GGG 38	-----	St-37/2	6 6	5	4.5	3.6								
10	GG-25	GGG 38	GS-45	St-37/2	10 10	8	7	6								
16	GG-25	GGG 38	GS-45	St-37/2	16 16	13	11	10								
	-----	-----	GS-C 25	C 22 N	16	14	13	11	10	8						
25	-----	GGG 38	GS-45.5	C 22 N	25 25	-----	18	16								
			GS-C 25		25	22	20	17	16	13						
			GS-22 Mo 4	15 Mo 3			25	22	20	19	18	17				
			GS-17 CrMo 55	13 Cr Mo 44					25	24	23	22	21	18	12	
40	-----	-----	GS-45.5	C 22 N	40 40	32	28	24								
			GS-C 25		40	35	32	28	24	21						
			GS-22 Mo 4	15 Mo 3			40	35	31	30	29	28				
			GS-17 CrMo 55	13 Cr Mo 44					40	38	36	35	33	29	19	
63	-----	-----	GS-C 25	C 22 N	63 63	36	29	24								
					63	50	45	40								
			GS-22 Mo 4	15 Mo 3			63	50	45	40	36	32				
			GS-17 CrMo 55	13 Cr Mo 44					64	56	50	47	46	45		
100	-----	-----	GS-C 25	C 22 N	100 100	80	70	60								
					100	80	70	60	56	50						
			GS-22 Mo 4	15 Mo 3			100	87	78	74	72	70				
			GS-17 CrMo 55	13 Cr Mo 44					100	95	91	89	87	74	62	
160	-----	-----	GS-C 25	C 22 N	160 160	130	112	96								
					160	130	112	96	90	80						
			GS-22 Mo 4	15 Mo 3			160	139	125	118	115	112				
			GS-17 CrMo 55	13 Cr Mo 44					160	153	146	142	139	118	79	
250	-----	-----	GS-C 25	C 22 N	250 250	200	175	150								
					250	200	175	150	140	125						
			GS-22 Mo 4	15 Mo 3			250	217	195	185	179	174				
			GS-17 CrMo 55	13 Cr Mo 44					250	238	227	223	217	184	124	54
												124	81			